

South Australia

Road Traffic (Miscellaneous) Variation Regulations 2009

under the *Road Traffic Act 1961*

Contents

Part 1—Preliminary

- 1 Short title
- 2 Commencement
- 3 Variation provisions

Part 2—Variation of *Road Traffic (Miscellaneous) Regulations 1999*

- 4 Variation of regulation 26—Wheels and tyres
-

Part 1—Preliminary

1—Short title

These regulations may be cited as the *Road Traffic (Miscellaneous) Variation Regulations 2009*.

2—Commencement

These regulations come into operation on the day on which they are made.

3—Variation provisions

In these regulations, a provision under a heading referring to the variation of specified regulations varies the regulations so specified.

Part 2—Variation of *Road Traffic (Miscellaneous) Regulations 1999*

4—Variation of regulation 26—Wheels and tyres

Regulation 26(5)(c)—delete ", provided that the rim diameter of a wheel fitted is not more than 50 millimetres greater than the largest diameter listed on the placard and not more than 50 millimetres less than the smallest diameter listed on the placard"

Note—

As required by section 10AA(2) of the *Subordinate Legislation Act 1978*, the Minister has certified that, in the Minister's opinion, it is necessary or appropriate that these regulations come into operation as set out in these regulations.

Made by the Governor

with the advice and consent of the Executive Council
on 3 September 2009

No 230 of 2009

MTR09/035